

Datasheet

Video indoor station for hands-free talking



Communication possibilities	
Voice transmission	Duplex and hands-free communication (Simplex if activated)
Audio privacy function	Yes
Automatic call cut-off	Yes
Number of selectable polyphone ring tones	13
Conversation and ringtone volume	Adjustable in the OSD menu 8 steps
Speaking time	45 s
Receive text messages	Yes (If connected to Nova software)
Number of internal calls	10
Number of parallel calls	1
Number of call diversion	1
Display data	
Size of display	17.8 cm (7.0")
Resolution	800 x 480 pixels
Type of display	Digital TFT display, color
Video privacy functions	Yes
Color intensity, brightness, contrast	Adjustable in the OSD menu 16 steps
Display time	60 s
OSD menu (on-screen-display-menu)	Yes, menu control by keys
Language	Danish, Swedish and English
Functions and adjustable parameters	
Functions through keys	Door release function, keypad light, ring tone mute, function key (can activate different functions depending on the installation), switching lights, image activation, camera selection, accept conversation (duplex communication), simplex communication (must be activated).
Adjustable parameters in the OSD menu	Ring tone volume, choice of ring tones, color saturation, brightness, contrast, key tone.
Functions available for installation in the OSD menu	Light switch function, internal call, parallel call, call diversion, door release automatic, control function, floor door release, AS address, reset to factory settings function.
Initial setup (connect doorstation button with indoor station)	With Service device or Manually

Housing	
Size	227 x 158 x 22mm
Recommended mounting height of display	160 cm
Mounting	Surface-mount
Material and color	ABS flamesecure plastic, white
Weight	650 g
Technical data	
Signal transmission and power supply	Polarity-free and short-circuit protected 2-wire BUS
Wiring technique (number of wires)	6 (a, b, P, M, V1, V2)
Power supply	26 V DC
Input current I(a)	I(a) = 0.5 mA
Input current I(P), standby	I(P) = 65 mA
Input current I(Pmax), max.	I(Pmax) = 340 mA
Mixed installation with audio and video in a system	Possible
Compatible with access control and Nova Software	Yes
Video image activation	AS-dependent
Acceptable ambient temperature	0 to + 40 °C
UV resistance	Unlimited