

## scantron

## Datasheet

PAK Audio door station with push buttons to the right



Audio door station PAK04

Communication features	
Push buttons (call destinations)	Max. 8
Information field	1 field (with up to three push buttons)
Communication time	56 s (adjustable)
Door standby time	56 s (adjustable)
Door release time at R-terminal	3 s (adjustable)
Acoustic parameters (adjustable)	Voice output volume and microphone sensitivity
Allocations per push button	Max. 2 serial numbers (indoor stations)
Light switch function	At any free push button (light symbol enclosed)
Commissioning and parameters	
Memory	Integrated
Configuration options	Manually, with Service Device or Software Configo™
Manually adjustable parameters	Call destination or light switch function, volume voice output, microphone sensitivity
Parameters adjustable with Service Device	Call destination or light switch function, communication time, change AS-address, block
Parameters adjustable with Software Configo™	Call destination or light switch function, communication time, door standby time, door release time, change AS-address, block
Initial setup (connect door station button with indoor station)	With Service device or manually
Technical data	
Signal transmission and power supply	Polarity-free and short-circuit protected 2-wire BUS
Wiring technique (number of wires)	2 (a,b) or 3 (a, b, P)
Additional terminal	R (for extended function door release)
Power supply	24 V DC
Input current I(a)	l(a) = 0.4 mA
Input current I(P), standby	I(P) = 11 mA
Input current I(Pmax), max.	l(Pmax)= 21 mA
Mixed installation with audio and video in a system	Possible
Compatible with access control and Nova Software	No
Acceptable ambient temperature	-20 to + 50 °C
UV resistance	Unlimited

## scantron

Housing	
Size	153 x 104 x 16 mm (PAK01) to 241 x 104 x 16 mm (PAK08)
Recommended mounting height of door station	160 cm
Mounting	Surface-mount
Rain shield available	Yes
Material and colour	Aluminium, anodized nature
Push buttons	Chrome-plated, made of full metal
Material name plate glas	Acrylic glass (shatterproof)
Size of name plates	19 x 62 mm (PAK03) to 53 x 62 (PAK01), templates available
Size of information field	19 x 62 mm (PAKO3) to 37 x 62 (PAKO2), templates available
Illumination, colour	Back-lit nameplate, white
Opening principle	Win:clip™
Weight	325 g (PAK01) to 600 g (PAK08)