

Datasheet

PES Audio doorstation with push buttons on both sides

PE-S: 460-002-00xx
DAT4062-EN



Audio doorstation PES08

Communication features	
Push buttons (call destinations)	From 4 to 20
Maximum call destinations with built-in extension (PET)	92
Maximum PET extension panels	4
Communication time	56 s (adjustable)
Door standby time	56 s (adjustable)
Door release time at R-terminal	3 s (adjustable)
Acoustic parameters (adjustable)	Voice output volume and microphone sensitivity
Allocations per push button	Max. 2 serial numbers (indoor stations)
Light switch function	At any free push button (light symbol enclosed)
Commissioning and parameters	
Plug-in memory	Changeable
Configuration options	Manually, with Service Device or Software Configo™
Manually adjustable parameters	Call destination or light switch function, volume voice output, microphone sensitivity
Parameters adjustable with Service Device	Call destination or light switch function, communication time, change AS-address, block
Parameters adjustable with Software Configo™	Call destination or light switch function, communication time, door standby time, door release time, change AS-address, block
Initial setup (connect doorstation button with indoor station)	With Service device or Manually
Technical data	
Signal transmission and power supply	Polarity-free and short-circuit protected 2-wire BUS
Wiring technique (number of wires)	2 (a,b) or 3 (a, b, P)
Additional terminal	R (for extended function door release)
Power supply	24 V DC
Mixed installation with audio and video in a system	Possible
Input current I(a)	I(a) = 0.4 mA
Input current I(P), standby	I(P) = 16 mA
Input current I(Pmax), max.	I(Pmax) = 65 mA
Compatible with access control and Nova Software	Yes (PES06 to PES20)
Acceptable ambient temperature	-20 to + 50 °C
UV resistance	Unlimited

Housing	
Size	280 x 135 x 21 mm (PES04) to 128 x 135 x 21 mm (PES20)
Recommended mounting height of doorstation	160 cm
Mounting	Surface-mount
Rain shield available	Yes
Info module available	Yes
Material and color	Aluminium, anodized nature
Push buttons	Chrome-plated, made of full metal
Material name plate glas	Acrylic glass (shatterproof)
Size of name plates	15 x 39 mm (template available)
Illumination, color	Back-lit nameplate, white
Opening principle	Concealed screws
Weight	600 g (PES04) to 1140 g (PES20)