

Datasheet

MI^X Compact audio/video door-station with LCD-display



MI^X Compact door-station

Communication features	
Push buttons (call destinations)	5
Push buttons (navigation)	3
Communication time	56s
Door standby time	56s
Door release time at R-terminal	4s (adjustable)
Acoustic parameters (adjustable)	Voice output volume and microphone sensitivity
Allocations per push button	Max. 2 serial numbers per destination
Light switch function	At any free push button (light symbol enclosed)
Commissioning and parameters	
Configuration options	Nova software
Manually adjustable parameters	Call destination or light switch function, volume voice output, microphone sensitivity
Parameters adjustable with Nova Software	Call destination or light switch function, communication time, change AS-address, block, door standby time, door release time.
Initial setup (connect door-station button with indoor station)	Nova software
Technical data	
Additional terminal	R (for extended function door release)
Power supply	24 V DC
Supply voltage	+24 V ± 8%
Additional power supply	580 mA
Input current I(a)	I(a) = 0.1 mA
Input current I(P), standby audio/video	I(P) = 43,5 mA / 84,2 mA
Input current I(Pmax), max. audio/video	I(Pmax)= 46,1 mA / 87 mA
Mixed installation with audio and video in a system	Possible
Compatible with access control and Nova Software	Yes
Acceptable ambient temperature	-25 to + 55 °C
UV resistance	Unlimited

Camera specifications	
Detecting angle	130°
Camera type	Colour
Resolution	380 TVL
Focal length f	2.0 mm (F=2.5)
Photo sensitivity	1 Lux (automatically switch between day/night vision)
Suitable by day and night	Yes (IR-camera)
Video-output	1.1 Vpp, symmetrical, 1 Vss FBAS
Housing	
Size (H x B x D)	Surface mounted: 375 x 140 x 25 mm <u>Flush-mounted in stainless steel, brass & titanium brass:</u> Front plate: 420 x 200 mm Back plate: 390 x 170 x 50 mm <u>Flush-mounted in RAL-colours:</u> Front plate: 440 x 200 mm Back plate: 410 x 170 x 49 mm
Recommended mounting height of door-station	160 cm
Mounting	Surface- or flush-mount
Material and colour	Surface-mounted: stainless steel Flush-mounted: stainless steel, brass, titanium brass, RAL-colours
Push buttons	Synthetic material with background light
Camera field	65 x 33 mm
Weight	2,0 kg
Display	
Resolution	298 x 384 pixels
Size of display	83 x 65 mm
Type of display	Graphic LCD
Language	Danish, Swedish & English (Nova software)
Display shows	Apartment number and two-lines of text
Number of call destinations	Up to 30 destinations
Background light	Yes
Heated	Yes
Material	Acryl, 2 mm
Reader	
Light diodes	Red and green
Reader	MIFARE
Loudspeaker	
Volume voice output, ringtone and microphone sensitivity	Yes (adjustable)