

# Datasheet

## Video indoor station for hands-free talking and fire announcement



Communication possibilities	
Voice transmission	Duplex and hands-free communication (Simplex if activated)
Audio privacy function	Yes
Automatic call cut-off	Yes
Number of selectable realsound ring tones	13
Conversation and ringtone volume	Adjustable in the OSD menu 4 steps
Speaking time	120 s
Receive text messages	Yes (If connected to Nova software)
Fire announcement	
Emergency announcement function installed	Yes
Possibility for two way emergency communication	Yes (depending on the system setup)
Maximum volume alarm tone at 1 meter	91 dBa
Maximum volume emergency announcement at 1 meter	80 dBa
Ignores ring tone mute settings at emergency announcement	Yes
Number of announcement groups per call destination	3
Display data	
Size of display	8,9 cm (3,5")
Resolution	320 x 234 pixels
Type of display	Active TFT display, color
Video privacy functions	Yes
Color intensity, brightness, contrast	Adjustable (8 steps)
Display time	80 s
OSD menu (on-screen-display-menu)	Yes, menu control by keys
Functions and adjustable parameters	
Functions through keys	Door release function, ring tone mute, switching lights, image activation, camera selection, accept conversation (duplex communication), simplex communication (must be activated).
Manually adjustable parameters	Ring tone mute, ring tone volume, ring tone selection, brightness, color saturation and contrast.
Parameters adjustable with Service Device	Light switch function, internal call, parallel call, call diversion, door release automatic, control function.
Parameters adjustable with Configo™	Simplex communication, ring tone selection, internal call, parallel call, call diversion, door release automatic, flat-door release function, control function, change AS-adress, reset to factory settings function.
Initial setup (connect doorstation button with indoor station)	With Service device or Manually
Dock station available	Yes

Technical data	
Signal transmission and power supply	Polarity-free and short-circuit protected 2-wire BUS
Wiring technique (number of wires)	6 (a, b, P, M, V1, V2)
Power supply	24 V DC
Input current I(a)	I(a) = 0.4 mA
Input current I(P), standby	I(P) = 16 mA
Input current I(Pmax), max.	I(Pmax) = 175 mA
Mixed installation with audio and video in a system	Possible
Compatible with access control and Nova Software	Yes
Video image activation	AS-dependent
Acceptable ambient temperature	0 to + 40 °C
UV resistance	Unlimited
Housing	
Size	186 x 101 x 20
Recommended mounting height of display	160 cm
Mounting	Surface-mount
Material and color	Plastic, white
Weight	230 g