

Datasheet

ANCHOR padlocks for SensoLock® oval cylinder mounting*



ANCHOR padlocks

*The SensoLock® electronic cylinder and oval cylinder house need to be purchased separately.



Certified by SBSC in Sweden
 Certificate No 04-598

ANCHOR Padlocks	
2283005 / 2283055	
Specifications	ANCHOR Padlock 830-3 B28/B50 with safety class 3 SSF / 4 EN in hardened steel with chrome surface. For Scandinavian oval cylinder body. For indoor fitting.
Dimensions	Shackle: Inner shackle height 28mm (B28) or 50mm (B50) Shackle 11mm diameter Body: Body thickness 60/25mm Body height 62mm
2283030 / 2283050	
Specifications	ANCHOR Padlock 830-3 B28/B50 WP safety class 3 SSF / 4 EN in hardened steel with chrome surface. For Scandinavian oval cylinder body. For outdoor fitting**
Dimensions	Schackle: Inner schackle height 28mm (B28) or 50mm (B50) Schackle 11mm diameter Body: Body thickness 60/25mm Body height 62mm
2280139 / 2280169 / 2280184	
Specifications	ANCHOR Padlock 802-2 B25/B60/B110 WP with safety class 2 SSF / 3 EN in brass with chrome surface. For Scandinavian oval cylinder body For outdoor fitting**
Dimensions	Shackle: Inner shackle height 25mm (B25), 60mm (B60) or 110mm (B110) Shackle 8mm diameter Body: Body thickness 50/25mm Body height 62mm

**available with a weather-resistant surface treatment, as well as O-rings, in order to avoid water ingress

Security Grade European Standard EN 12320 / Swedish Padlock Class Standard SSFN014***			
Requirements (safety class)	2 SFF/3 EN	3 SFF/4 EN	
Corrosion, salt spray (time)	24	96	h
Key retained in open position	No	Yes	
Minimum number of differs	2500	5000	
Non-interpassing of keys with just one interval differ – Torque on key	1,5	1,5	Nm
Load on cylinder plug or locking mechanism	4	5	kN
Torque resistance of cylinder plug	5	15	Nm
Pulling of shackle/staple	15	30	kN
Twisting of shackle/staple	200	450	Nm
Cutting of shackle/staple	25	35	kN
Blow on lock body and shackle/staple (wight/g x height/mm)	1250x800	3050x1000	x5
Test temperature	-20°C	-20°C	
Drilling	-	2	min
Sawing	-	2	min
Lock picking and tampering***	2 simple tools	10 simple tools	min
Attack with manual tools***	-	5	min

SensoLock® MIFARE offline

716-002-0000



Specifications	SensoLock®66 MIFARE offline lock cylinder (716-002-0000) for outdoor use with 3 LED for signalling, 2 units. CR-2 Lithium batteries.
Dimensions	IP66/45mm diameter

701-000-1000

Specifications	Scandinavian oval cylinder house made in chromeplated brass.
----------------	--

Add-ons

2150213



Specifications	ANCHOR Padlock chain in stainless steel for 8mm shackle. Wall mounting.
Dimensions	Chain diameter: 4mm Chain length: 400mm

2150212

Specifications	ANCHOR Padlock chain in stainless steel for 11mm shackle Wall mounting.
Dimensions	Chain diameter: 4mm Chain length: 400mm

701-000-1011



Specifications	Vandal-resistant shield for the padlock made in PA6G30 polycarbonate with 2 shells and 4 oneway bolts and 4 safety nuts
Dimensions	B90 x H80